



www.premiercoatings.com

## PRODUCT DATA SHEET

Headcorn Road · Smarden · Ashford · Kent · TN27 8PJ · United Kingdom  
Telephone: + 44 (0) 1233 770 663 · Fax: + 44 (0) 1233 770 633  
E-mail: enquiries@premiercoatings.com

### PREMBOND COLOURFLEX MASTIC

**DESCRIPTION** A cold applied mastic for profiling of irregularly shaped fittings prior to application of Prembond Colourflex Tape. Light density, non-staining and non-sagging over wide temperature range. Recommended for application around pipe fittings to provide a suitable profile for the application of Prembond Colourflex Tape particularly for above ground applications where resistance to staining and sagging are important.

**COMPOSITION** A petrolatum based compound containing beads of cellular polymer, pigments and flow control additives. It contains no volatile components.

TYPICAL PROPERTIES	DATA
<b>Colour</b>	Light stone
<b>Specific Gravity</b>	0.7
<b>Specific Volume</b>	1430 cc/kg
<b>Solids Content</b>	100%
<b>Flash Point</b>	>185°C
<b>Sag Temperature</b>	>75°C
<b>Shelf Life</b>	5 years
<b>Temperature Range</b> <i>For Application</i> <i>For Service</i>	0°C to 45°C -25°C to 65°C

  

<b>RECOMMENDED PRIMER</b>	None required
---------------------------	---------------

Note - the Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.

Note - the Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.