



www.premiercoatings.com

# PRODUCT DATA SHEET

Headcorn Road · Smarden · Ashford · Kent · TN27 8PJ · United Kingdom  
Telephone: + 44 (0) 1233 770 663 · Fax: + 44 (0) 1233 770 633  
E-mail: enquiries@premiercoatings.com

## PREMBOND HI-HEAT TAPE

**DESCRIPTION** Cold applied conformable fabric based tape for the corrosion protection of pipes operating at elevated temperatures. Suitable for the protection of copper, iron or steel pipes above ground in ducts or set in concrete.

**COMPOSITION** Non-rotting synthetic fibre fabric impregnated and coated with a compound based on petrolatum and synthetic polymers and having a clear plastics film backing.

TYPICAL PROPERTIES	DATA
<b>Colour</b>	Red/Brown
<b>Breaking Strength</b>	200 N/50mm minimum
<b>Elongation at Break</b>	15%
<b>Breakdown Voltage</b>	16 kV minimum per double layer
<b>Temperature Range</b> <i>For Application</i> <i>For Service</i>	5°C to 50°C 110°C maximum
<b>Roll Length</b>	10m rolls
<b>Width</b>	50mm to 300mm
<b>Total Thickness</b>	1.4mm
<b>Weight</b>	1.44kg/m <sup>2</sup>

Note - the Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.

Note - the Typical Data shown in this leaflet is intended as a general guide and is based on tests carried out under controlled conditions. For further information on Product Specification consult Premier Coatings Ltd.