

Premcote Primer

Specialised primer designed for use with the Premier pipe-wrapping tapes

Composition

A bitumen-based primer solution.

Uses

Premcote Primer is a low viscosity, fast-drying primer that maintains surface cleanliness of the pipe prior to tape application. It promotes a strong bond development between the substrate and Premier bitumen tapes.

Service Temperature: up to +75°C

Characteristics

Premcote Primer:

- improves cathodic disbondment resistance,
- provides excellent adhesion of Premier bitumen tapes to the substrate, and
- dries rapidly even in cool conditions.

Surface Preparation

Surfaces must be clean, dry and free from rust, scale, grease, non-adherent coatings and other contamination. Preferably, the area will be grit blasted or well wire brushed.

Typical Properties

Colour	Black
Viscosity	200-500 cP
Solid Content	59% w/w
Flash Point	>23°C
Specific gravity	0.94
Drying time	10-15 minutes
Surface coverage	9-11 m ² /L
VOC	<440 g/L

Application

Thorough stirring of the primer is recommended prior to use. Use a brush or roller to apply the primer. Ensure product container is sealed air-tight between uses. See *Instructions for Use* for additional detail. See Product Safety Data Sheet for recommended safety precautions.

Application Temperature: 0°C to +55°C.

Availability

5 L, 25 L and 200 L drums

Storage Conditions

Store all components upright in original packaging in a cool, dry, area. Keep away from heat, sparks and open flames. Keep container sealed air-tight.

Waste material

Please apply the waste hierarchy to minimise or avoid waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).

Page 1 of 1

Revision date: 23/09/2025