

Premier Acrylic Topcoat

A component of the Premier Steelcoat Systems for the protection of above ground steelwork and storage tanks

Composition

Single pack waterborne synthetic acrylic copolymer coating.

Uses

Premier Acrylic Topcoat is used as a topcoat over Premier Ultraseal Tape and Premier Ultraseal RT Tape as part of the Premier Steelcoat Systems, providing an excellent weatherproof membrane.

Service Temperature: -20°C to +80°C

Characteristics

Premier Acrylic Topcoat is:

- weather-resistant,
- excellent adhesion,
- protected against biofilm attack,
- low VOC,
- remains flexible throughout service life,
- UV resistant, and
- single component.

Application

See *Instructions for Use* for additional information.
Ensure surfaces are clean and dry before

application. Apply by brush or roller. Two coats are recommended with Premier Steelcoat Systems.

Application Temperature: +3°C to +40°C

Availability

Premier Acrylic Topcoat is available in 15 L drums in white, black and grey colours. Other colours may be available on request.

Cleaning

Clean brushes and tools with water immediately after use.

Storage Conditions

Store in original packaging. Store in dry, cool, frost-free, well ventilated condition, out of direct sunlight and other major sources of heat. Expected shelf life approximately 2 years.

Waste material

Please apply the waste hierarchy to avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Specific gravity	1.35
Solids (volume)	49%
VOC content	<0.07% by mass
Coverage (over Premier Ultraseal Tape or Premier Ultraseal RT Tape)	3 m ² /litre
Drying time	
at +20°C	3 hours
at +3°C	24 hours

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).

Page 1 of 1

Revision date: 10/10/2023