

Premier PVC Self-Adhesive Tape 250

Composition

Premier PVC Self-Adhesive Tape 250 consists of a PVC film coated on one side with self-adhesive.

Uses

Premier PVC Self-Adhesive Tape 250 is a self-adhesive tape used as an outer layer to provide additional mechanical and UV protection to the Premtape range of anti-corrosion tapes.

Service Temperature: -5°C to +60°C with a short-term peak at +80°C

Characteristics

Premier PVC Self-Adhesive Tape 250 is:

- highly conformable,
- highly elongated at break,
- suitable for hand application, and
- suitable for machine application.

Application

Wrap spirally over used Premtape, ensuring sufficient tension and overlap while avoiding creases and folds.

Application temperature: +5°C to +40°C

Typical Properties

Thickness	0.25 mm	ASTM D1000
Weight	0.33 kg/m ²	
Tensile strength at break	5 N/mm	ASTM D1000
Elongation at break	150%	ASTM D1000
Tear strength	15 N	ASTM D1004
Adhesion Peel strength		
<i>To self</i>	0.4 N/mm	ASTM D1000
<i>To steel</i>	0.4 N/mm	
Dielectric strength (double layer)	20 kV minimum	ASTM D1000

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).

Page 1 of 1

Revision date: 17/07/2024