

Premstik & Premstik LT (Double-Sided Tape)

Composition

Self-adhesive double-sided tape. Comprising a layer of rubberised bitumen. Two separate interleaves are present.

Uses

Suitable for use in conjunction with the Premseal waterproofing membrane system. May be used as a jointing tape for building membranes – consult manufacturer for compatibility.

Service Temperature: -20°C to +35°C

Characteristics

Solvent Free.
Non-Shrinking.

Application

Ensure surfaces are clean and dry.
Remove interleaves before use.
Apply pressure to ensure adhesion.

Application Temperature: +5°C to +30°C

Availability

Available in wider interleave for ease of use.
Available in Low Temperature grade for easier use at low temperatures (less than +10°C).

Storage Conditions

Store in original packaging. Store in dry, cool, well ventilated condition, out of direct sunlight and other major sources of heat.

Expected Shelf Life

Approximately 2 years

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical properties

Appearance	Rolls
Adhesive Thickness	1.0, 1.5, 2.0 mm
Width	50, 100, 150 mm
Length	10, 50, m

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).