

Premtape Hotline

Corrosion protection of pipes at elevated temperatures

Composition

Premtape Hotline consists of a synthetic fibre fabric impregnated and coated with a compound based on petrolatum and synthetic polymers and laminated to a clear plastic backing.

Uses

Premtape Hotline is a cold-applied conformable tape for the corrosion protection of pipes operating at elevated temperatures.

Premtape Hotline is suitable for the protection of copper, iron or steel pipes above ground in ducts or set in concrete. For below ground applications, please refer to the manufacturer as a high-temperature outerwrap is recommended.

Characteristics

Premtape Hotline is:

- VOC free,
- easy to apply, and
- suitable for service up to +110°C

Application

See *Instructions for use* for additional detail.
Recommended primer: Primer not required

Application Temperature: +5°C to +50°C

Availability

Premtape Hotline is available in 10 meter rolls in widths from 50 mm to 300 mm.

Storage conditions

Store in a cool and dry place in original packaging.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Colour	Red/Brown
Thickness	1.4 mm
Weight	1.44 kg/m ²
Breaking strength	200 N/ 50 mm width
Elongation at break	15%
Breakdown voltage (double layer)	16 kV

Note: For buried pipe applications, a compatible high-temperature outerwrap, such as Premcote Glass Outerwrap, is recommended.

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).