

TECHNICAL DATA SHEET

LEADERS IN CORROSION PREVENTION & SEALING TECHNOLOGY



Premtape Hi-Tack Primer

Specialised primer designed for use with the Premier petrolatum pipe-wrapping tapes

Composition

Premtape Hi-Tack Primer is comprised of high melting point petrolatum in hydrocarbon solvent supplied as a semi-solid paste for brush application.

Uses

Premtape Hi-Tack Primer is a tacky, adhesive primer for use with the Premier petrolatum tapes – particularly where these are applied longitudinally or on flat areas. It is a component of the Steelcoat 100 System.

Surface Preparation

Surfaces must be clean, dry and free from rust, scale and non-adherent coatings. Rusted areas should be mechanically cleaned to St2. Surfaces may be damp, but must not have droplets or a continuous film of water.

Application

See Instructions for Use for further details. Apply Premtape Hi-Tack Primer evenly over the surface at a wet film thickness (WFT) of 200 μ m. Recommended dry film thickness (DFT) is 140 μ m.

Application Temperature: 0°C to +55°C.

Availability

5 L, 25 L and 200 L drums

Storage Conditions

Store all components upright in original packaging in a cool, dry, area. Keep away from heat, sparks and open flames.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Solids	70%
Flash Point	>32°C
Specific gravity	0.91
Drying time	60 minutes
Surface coverage	5 m²/L
VOC	<330 g/L

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).

PREMIER COATINGS LTD Headcorn Road, Smarden, Ashford, Kent, TN27 8PJ United Kingdom



Page 1 of 1 Revision date: 14/10/2022

TEL: +44 (0) 1233 770 663 FAX: +44 (0) 1233 770 633 WEB: www.premiercoatings.com EMAIL: enquiries@premiercoatings.com