

# Premtape Hi-Tack

Corrosion protection tape

## Composition

Premtape Hi-Tack consists of a non-woven synthetic fibre fabric impregnated and coated with an adhesive compound based on petrolatum, polymers and inert siliceous fillers.

## Uses

Premtape Hi-Tack is a specially formulated high tack cold applied petrolatum tape for high performance corrosion protection of above ground steelwork. It is a component of the Premier Steelcoat system.

Service Temperature: -25°C to +65°C

## Characteristics

Premtape Hi-Tack is:

- VOC free,
- highly resistant to acids, alkali and salts, and
- easy to apply.

## Primer

Premier Hi-Tack Primer

## Application

See *Instructions for Use* for additional detail.

Application Temperature: +5°C to +50°C.

## Availability

Premtape Hi-Tack is available in 10m rolls in widths from 50 mm to 450 mm.

Additional sizes may be available on request.

## Storage conditions

Store in a cool and dry place in original packaging.

## Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

## Typical Properties

Thickness	1.15 mm	ASTM D 1000
Weight	1.44 kg/m <sup>2</sup>	
Breaking strength	4 N/mm	ASTM D 1000
Elongation at break	6%	ASTM D 1000
Breakdown voltage (55% overlap)	16 kV	

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 677780).