

Premtape LD Mastic

Cold-applied, self-supporting mastic

Composition

Premtape LD Mastic is a petrolatum compound containing cellular polymer beads and flow control additives.

Uses

Premtape LD Mastic is designed for moulding around irregularly shaped fittings to provide a suitable profile for applying anti-corrosion tapes.

Premtape LD Mastic is used with primer, prior to overwrapping with Premtape, Premcote and Prembond tapes for long term corrosion protection of buried pipe fittings.

Service temperature: up to +70°C

Characteristics

Premtape LD Mastic is:

- Low density,
- Resistant to slumping, and
- Suitable for deeply filled joints and valves.

Surface preparation

See *Instructions for Use* for additional detail.

Surfaces must be clean, dry and dust-free.

Primer

Prempaste or Prembond Hi-Tack Primer

Application

See *Instructions for Use* for additional detail.

Press Premtape LD Mastic into cavities, angles and around bolt heads to form a profile suitable for wrapping with tape without forming bridges or voids.

Application temperature: 0°C to +45°C

Availability

Premtape LD Mastic is available in:
6 x 1.75 kg rectangular slabs per carton
4 x 3.5 kg rectangular slabs per carton

Storage conditions

Store in a cool dry place in original packaging.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical properties

Colour	Yellow/ cream with white spheres
Specific gravity	0.605
Specific volume	1.65 dm ³ /kg

Important: Premier Coatings Ltd. pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Premier Coatings Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. Q09303) and an Environmental Management System registered to BS EN ISO 14001 (BSI Certificate no. EMS 67780).