

STEELCOAT 200™ SYSTEM



A petrolatum tape system for the protection of above ground pipelines operating at elevated service temperatures

The Steelcoat 200™ System comprises a polymer backed petrolatum tape (Premtape Hotline™) and a high temperature mastic for sealing fittings in awkward shapes (Premier 16A™). No primer is required.

The system is designed to protect copper, iron or steel pipes that run at high temperatures, up to 110°C maximum (90°C if the pipe is buried), located above ground in ducts or set in concrete.

FEATURES

- No primer required
- Cold applied
- For service temperatures up to 110°C maximum
- Surface tolerant
- Can be applied by hand or wrapping machine

COMPONENTS

Premtape Hotline™

Applied with a 55% overlap by either hand or machine application.

Premier 16A™

SURFACE PREPARATION

Minimal surface preparation required. Surfaces must be clean and dry. Remove all loose rust, scale and flaking coatings by hand wire brush.



PUB No. 510.05.2021

PREMIER COATINGS LIMITED

TEL: +44 (0) 1233 770 663

EMAIL: enquiries@premiercoatings.com

WEB: www.premiercoatings.com

Headcorn Rd Smarden,

Ashford, TN27 8PJ

UNITED KINGDOM



THE QUEEN'S AWARDS
FOR ENTERPRISE
INTERNATIONAL TRADE
2017



Q 09303 | EMS 677780
ISO 9001:2015 & ISO 14001:2015



UKAS
MANAGEMENT
SYSTEMS
0003



A MEMBER OF WINN & COALES INTERNATIONAL